






Cisco Firepower Next-Generation Firewall

The Cisco Firepower™ Next-Generation Firewall (NGFW) is the industry's first fully integrated, threat-focused next-gen firewall with unified management. It includes Application Visibility and Control (AVC), optional Firepower next-gen IPS (NGIPS), Cisco® Advanced Malware Protection (AMP), and URL Filtering. Cisco Firepower NGFW provides advanced threat protection before, during, and after attacks.

	Stop more threats	Contain known and unknown malware with leading Cisco AMP and sandboxing. Get application firewalling (AVC) for 4000 commercial applications, plus additional custom applications.
	Gain more insight	Gain superior visibility into your environment with Cisco Firepower next-gen IPS. Automated risk rankings and impact flags identify priorities for your team.
	Detect earlier, act faster	The Cisco Annual Security Report identifies a 100-day median time from infection to detection, across enterprises. Cisco reduces this time to less than a day.
	Reduce complexity	Get unified management and automated threat correlation across tightly integrated security functions, including application firewalling, NGIPS, and AMP.
	Get more from your network	Enhance security, and take advantage of your existing investments, with optional integration of other Cisco and third-party networking and security solutions.

Performance Highlights

Table 1 summarizes the performance highlights of the Cisco Firepower NGFW 4100 Series and 9300 appliances and select ASA-FTD-5500-X appliances.

Table 1. Performance Highlights

Features	Cisco Firepower Model							Cisco ASA 5500-FTD-X Model							
	4110	4120	4140	4150 ¹	9300 with 1 SM-24 Module	9300 with 1 SM-36 Module	9300 with 3 SM-36 Modules	5506-FTD-X	5506W-FTD-X	5506H-FTD-X	5508-FTD-X	5516-FTD-X	5525-FTD-X	5545-FTD-X	5555-FTD-X
Firewall throughput (ASA)	20 Gbps	40 Gbps	60 Gbps	-	75 Gbps	80 Gbps	225 Gbps	750 Mbps	750 Mbps	750 Mbps	1 Gbps	1.8 Gbps	2 Gbps	3 Gbps	4 Gbps
Throughput FW + AVC (Firepower Threat Defense)²	12 Gbps	20 Gbps	25 Gbps	-	25 Gbps	35 Gbps	100 Gbps	250 Mbps	250 Mbps	250 Mbps	450 Mbps	850 Mbps	1,100 Mbps	1,500 Mbps	1,750 Mbps
Throughput: FW + AVC + NGIPS (Firepower Threat Defense)²	10 Gbps	15 Gbps	20 Gbps	-	20 Gbps	30 Gbps	90 Gbps	125 Mbps	125 Mbps	125 Mbps	250 Mbps	450 Mbps	650 Mbps	1,000 Mbps	1,250 Mbps

¹ Cisco Firepower 4150 is scheduled for release in the first half of 2016; specifications to be announced

² HTTP sessions with average packet size of 1024-bytes



Cisco Firepower 4100 Series:
The industry's first 1RU NGFWs with 40-GbE interfaces



Cisco Firepower 9300:
Ultra-high-performance NGFW, expandable as your needs grow



Cisco ASA 5500-X Series:
Compact models for branch offices, industrial applications and the Internet edge

Platform Support

Cisco Firepower 4100 Series and Firepower 9300 NGFW appliances use the Cisco Firepower Threat Defense software image. Alternatively, these appliances can support the Cisco Adaptive Security Appliance (ASA) software image. The Cisco Firepower Management Center (formerly FireSIGHT) provides unified management of the Cisco Firepower NGFW, as well as Cisco Firepower NGIPS and Cisco AMP. Also available, on select Cisco Firepower appliances, and direct from Cisco, is the Radware DefensePro distributed denial of service (DDoS) mitigation capability.

Cisco Firepower 4100 Series Appliances

The Cisco Firepower 4100 Series is a family of four threat-focused NGFW security platforms. Their maximum throughput ranges from 20 to more than 60 Gbps, addressing use cases from the Internet edge to the data center. They deliver superior threat defense, at faster speeds, with a smaller footprint.

Cisco Firepower 9300 Appliance

The Cisco Firepower 9300 is a scalable (beyond 1Tbps), carrier-grade, modular platform designed for service providers, high-performance computing centers, data centers, campuses, high-frequency trading environments, and more that require low (less than 5-microsecond offload) latency and exceptional throughput. Cisco Firepower 9300 supports flow-offloading, programmatic orchestration, and management of security services with RESTful APIs. It is also available in NEBS-compliant configurations.

Cisco ASA 5500-FTD-X Series Appliances

The Cisco ASA 5500-FTD-X Series is a family of eight threat-focused NGFW security platforms. Their maximum throughput ranges from 750 Mbps to 4 Gbps, addressing use cases from the small or branch office to the Internet edge. They deliver superior threat defense in a cost-effective footprint.

Performance Specifications and Feature Highlights

Table 2 summarizes the capabilities of the Cisco Firepower NGFW 4100 Series and 9300 appliances and the Cisco ASA 5500-FTD-X appliances when running the Cisco Firepower Threat Defense image.

Table 2. Performance Specifications and Feature Highlights with the Firepower Threat Defense Image

Cisco Firepower Model								Cisco ASA 5500-FTD-X Model							
Features	4110	4120	4140	4150 ¹	9300 with 1 SM-24 Module	9300 with 1 SM-36 Module	9300 with 3 Clustered SM-36 Modules	5506-FTD-X	5506-W-FTD-X	5506H-FTD-X	5508-FTD-X	5516-FTD-X	5525-FTD-X	5545-FTD-X	5555-FTD-X
Throughput : FW + AVC²	12 Gbps	20 Gbps	25 Gbps	-	25 Gbps	35 Gbps	100 Gbps	250 Mbps	250 Mbps	250 Mbps	450 Mbps	850 Mbps	1,100 Mbps	1,500 Mbps	1,750 Mbps
Throughput : AVC + IPS²	10 Gbps	15 Gbps	20 Gbps	-	20 Gbps	30 Gbps	90 Gbps	125 Mbps	125 Mbps	125 Mbps	250 Mbps	450 Mbps	650 Mbps	1,000 Mbps	1,250 Mbps
Sizing throughput (450-byte HTTP)³: AVC or IPS	4 Gbps	8 Gbps	10 Gbps	-	9 Gbps	12.5 Gbps	30 Gbps								
Sizing throughput (440-byte HTTP)³: AVC or IPS								90 Mbps	90 Mbps	90 Mbps	180 Mbps	300 Mbps	375 Mbps	575 Mbps	725 Mbps
Maximum concurrent sessions, with AVC	4.5 million	11 million	14 million	-	28 million	29 million	57 million	50000	50000	50000	100,000	250,000	500,000	750,000	1,000,000
Maximum new connections per second, with AVC	68,000	120,000	160,000	-	120,000	160,000	500,000	5,000	5,000	5,000	10,000	20,000	20,000	30,000	50,000
Application Visibility and Control (AVC)	Standard, supporting more than 4000 applications, as well as geo-locations, users, and websites														
AVC: OpenAppID support for custom, open source, application detectors	Standard														
Cisco Security Intelligence	Standard, with IP, URL, and DNS threat intelligence														
Cisco Firepower NGIPS	Available; can passively detect endpoints and infrastructure for threat correlation and indicators of compromise (IoC) intelligence														
Cisco AMP for Networks	Available; enables detection, blocking, tracking, analysis, and containment of targeted and persistent malware, addressing the attack continuum both during and after attacks. Integrated threat correlation with Cisco AMP for Endpoints is also optionally available														
Cisco AMP Threat Grid sandboxing	Available														
URL Filtering: categories	More than 80+														
URL Filtering: URLs categorized	More than 280 million														

Cisco Firepower Model								Cisco ASA 5500-FTD-X Model							
Features	4110	4120	4140	4150 ¹	9300 with 1 SM-24 Module	9300 with 1 SM-36 Module	9300 with 3 Clustered SM-36 Modules	5506-FTD-X	5506-W-FTD-X	5506H-FTD-X	5508-FTD-X	5516-FTD-X	5525-FTD-X	5545-FTD-X	5555-FTD-X
Automated threat feed and IPS signature updates	Yes: class-leading Collective Security Intelligence (CSI) from Cisco Talos (http://www.cisco.com/c/en/us/products/security/talos.html)														
Third-party and open-source ecosystem	Open API for integrations with third-party products; Snort [®] and OpenAppID community resources for new and specific threats														
Centralized management	Centralized configuration, logging, monitoring, and reporting is performed by the Firepower Management Center														
High availability and clustering	Active/standby; with Cisco Firepower 9300 intra-chassis clustering is also supported														
VLANs - Maximum	1024														

¹ Cisco Firepower 4150 is scheduled for release in the first half of 2016; specifications to be announced.

² HTTP sessions with average packet size of 1024-bytes.

³ Performance will vary depending on features activated and network traffic protocol mix and packet size characteristics.

Table 3 summarizes the performance and capabilities of the Cisco Firepower 4100 Series and 9300 appliances when running the ASA image. For Cisco ASA 5500-X series ASA performance specifications please visit the [Cisco ASA with FirePOWER Services data sheet](#).

Table 3. ASA Performance and Capabilities

Cisco Firepower Model							
Features	4110	4120	4140	4150 ¹	9300 with 1 SM-24 Module	9300 with 1 SM-36 Module	9300 with 3 SM-36 Modules
Stateful inspection firewall throughput²	20 Gbps	40 Gbps	60 Gbps	-	75 Gbps	80 Gbps	225 Gbps
Stateful inspection firewall throughput (multiprotocol)³	10 Gbps	20 Gbps	30 Gbps	-	50 Gbps	60 Gbps	130 Gbps
Concurrent firewall connections	10 million	15 million	25 million	-	55 million	60 million	70 million
Firewall latency (UDP 64b, microseconds)	3.5	3.5	3.5	-	3.5	3.5	3.5
New connections per second	150,000	250,000	350,000	-	600,000	900,000	2.5 million
Security contexts⁴	250	250	250	-	250	250	250
Virtual interfaces	1024	1024	1024	-	1024	1024	1024

Cisco Firepower Model							
Features	4110	4120	4140	4150 ¹	9300 with 1 SM-24 Module	9300 with 1 SM-36 Module	9300 with 3 SM-36 Modules
IPSEC VPN throughput	8 Gbps	10 Gbps	14 Gbps	-	15 Gbps	18 Gbps	54 Gbps ⁵
IPsec/Cisco AnyConnect/Apex site-to-site VPN peers	10,000	15,000	20,000	-	20,000	20,000	60,000 ⁵
Maximum number of VLANs	1024	1024	1024	-	1024	1024	1024
Security contexts (included; maximum)	10; 250	10; 250	10; 250	-	10; 250	10; 250	10; 250
High availability	Active/active and active/standby	Active/active and active/standby	Active/active and active/standby	-	Active/active and active/standby	Active/active and active/standby	Active/active and active/standby
Clustering	Up to 15 appliances	Up to 15 appliances	Up to 15 appliances	-	Up to 5 appliances with 3 security modules each	Up to 5 appliances with three security modules each	Up to 5 appliances with 3 security modules each
Scalability	VPN clustering and load balancing, interchassis clustering	VPN clustering and load balancing, interchassis clustering	VPN clustering and load balancing, interchassis clustering	-	VPN clustering and load balancing, intrachassis clustering, interchassis clustering	VPN clustering and load balancing, intrachassis clustering, interchassis clustering	VPN clustering and load balancing, intrachassis clustering, interchassis clustering

¹ Cisco Firepower 4150 is scheduled for release in the first half of 2016; specifications to be announced.

² Throughput measured with User Datagram Protocol (UDP) traffic measured under ideal test conditions.

³ "Multiprotocol" refers to a traffic profile consisting primarily of TCP-based protocols and applications like HTTP, SMTP, FTP, IMAPv4, BitTorrent, and DNS.

⁴ Available for the firewall feature set.

⁵ In unclustered configuration.

Hardware Specifications

Tables 4 and 5 summarize the hardware specifications for the 4100 Series and 9300, respectively. Table 6 summarizes regulatory standards compliance. For Cisco ASA 5500-X series hardware specifications please visit the [Cisco ASA with FirePOWER Services data sheet](#).

Table 4. Cisco Firepower 4100 Series Hardware Specifications

Cisco Firepower Model				
Features	4110	4120	4140	4150
Dimensions (H x W x D)	1.75 x 16.89 x 29.7 in. (4.4 x 42.9 x 75.4 cm)			
Form factor (rack units)	1RU			
Security module slots	N/A			
I/O module slots	2			
Supervisor	Cisco Firepower 4000 Supervisor with 8 x 10 Gigabit Ethernet port and 2 network module (NM) slots for I/O expansion			
Network modules	<ul style="list-style-type: none"> 8 x 10 Gigabit Ethernet Enhanced Small Form-Factor Pluggable (SFP+) network module 4 x 40 Gigabit Ethernet Quad SFP+ network module 			
Maximum number of interfaces	Up to 24 x 10 Gigabit Ethernet (SFP+) interfaces; up to 8 x 40 Gigabit Ethernet (QSFP+) interfaces with 2 network modules			

Cisco Firepower Model					
Features	4110	4120	4140	4150	
Integrated network management ports	1 x Gigabit Ethernet copper port				
Serial port	1 x RJ-45 console				
USB	1 x USB 2.0				
Storage	200 GB	200 GB	400 GB	400 GB	
Power supplies	Configuration	Single 1100W AC, dual optional. Single/dual 950W DC optional ^{1,2}	Single 1100W AC, dual optional. Single/dual 950W DC optional ^{1,2}	Dual 1100W AC ¹	Dual 1100W AC ¹
	AC input voltage	100 to 240V AC			
	AC maximum input current	13A			
	AC maximum output power	1100W			
	AC frequency	50 to 60 Hz			
	AC efficiency	>92% at 50% load			
	DC input voltage	-40V to -60VDC			
	DC maximum input current	27A			
	DC maximum output power	950W			
	DC efficiency	>92.5% at 50% load			
Redundancy	1+1				
Fans	6 hot-swappable fans				
Noise	78 dBA				
Rack mountable	Yes, mount rails included (4-post EIA-310-D rack)				
Weight	36 lb (16 kg): 2 x power supplies, 2 x NMs, 6x fans; 30 lb (13.6 kg): no power supplies, no NMs, no fans				
Temperature: operating	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)	32 to 95°F (0 to 35°C), at sea level	32 to 95°F (0 to 35°C), at sea level	
Temperature: nonoperating	-40 to 149°F (-40 to 65°C)				
Humidity: operating	5% to 95% noncondensing				
Humidity: nonoperating	5% to 95% noncondensing				
Altitude: operating	10,000 ft. (max)		10,000 ft. (max)		
Altitude: nonoperating	40,000 ft. (max)				

¹ Dual Power Supplies are hot-swappable.

² DC power option is expected on Cisco Firepower 4110 and 4120 in the second half of 2016.

Table 5. Cisco Firepower 9300 Hardware Specifications

Specification	Description
Dimensions (H x W x D)	5.25 x 17.5 x 32 in. (13.3 x 44.5 x 81.3 cm)
Form factor	3 rack units (3RU), fits standard 19-in. (48.3-cm) square-hole rack
Security module slots	3
Network module slots	2 (within supervisor)
Supervisor	Cisco Firepower 9000 Supervisor with 8 x 10 Gigabit Ethernet port and 2 network module slots for I/O expansion

Specification	Description		
Security modules	<ul style="list-style-type: none"> • Cisco Firepower 9000 Security Module 24 with 2 x SSDs in RAID-1 configuration • Cisco Firepower 9000 Security Module 36 with 2 x SSDs in RAID-1 configuration 		
Network modules	<ul style="list-style-type: none"> • 8 x 10 Gigabit Ethernet Enhanced Small Form-Factor Pluggable (SFP+) network module • 4 x 40 Gigabit Ethernet Quad SFP+ network module • 2 x 100 Gigabit Ethernet Quad SFP28 network module (double-wide, occupies both network module bays) 		
Maximum number of interfaces	Up to 24 x 10 Gigabit Ethernet (SFP+) interfaces; up to 8 x 40 Gigabit Ethernet (QSFP+) interfaces with 2 network modules		
Integrated network management ports	1 x Gigabit Ethernet copper port (on supervisor)		
Serial port	1 x RJ-45 console		
USB	1 x USB 2.0		
Storage	Up to 2.4 TB per chassis (800 GB per security module in RAID-1 configuration)		
Power supplies	AC power supply	-48V DC power supply	
	Input voltage	200 to 240V AC	-40V to -60V DC [*]
	Maximum input current	15.5A to 12.9A	69A to 42A
	Maximum output power	2500W	2500W
	Frequency	50 to 60 Hz	-
	Efficiency (at 50% load)	92 percent	92 percent
	Redundancy	1+1	
Fans	4 hot-swappable fans		
Noise	75.5 dBA at maximum fan speed		
Rack mountable	Yes, mount rails included (4-post EIA-310-D rack)		
Weight	105 lb (47.7 kg) with one security module; 135 lb (61.2 kg) fully configured		
Temperature: Standard Operating	Up to 10,000 ft. (3000 M): 32 to 104°F (0 to 40°C) for SM-24 module 32 to 88°F (0 to 35°C) for SM-36 module at sea-level Altitude adjustment notes: For SM-36, maximum temp is 35°C, for every 1000 feet above sea level subtract 1°C		
Temperature: NEBS Operating	Long Term: 0 to 45°C up to 6000 ft. (1829 m) Long Term: 0 to 35°C, 6000-13000 ft. (1829-3964 m) Short Term: -5 to 55°C, up to 6000 ft. (1829 m) Note: Firepower 9300 NEBS Compliance applies only to SM-24 configurations		
Temperature: nonoperating	-40 to 149°F (-40 to 65°C); maximum altitude is 40,000 ft.		
Humidity: operating	5 to 95 percent noncondensing		
Humidity: nonoperating	5 to 95 percent noncondensing		
Altitude: operating	SM-24: 0 to 13,000 ft. (3962 m) SM-36: 0 to 10,000 ft. (3048 m); please see above Operating Temperature section for temperature adjustment notes		
Altitude: nonoperating	40,000 ft. (12,192 m)		

^{*} Minimum turn-on voltage is -44V DC

Table 6. Cisco Firepower 4100 Series and Cisco Firepower 9300 NEBS, Regulatory, Safety, and EMC Compliance

Specification	Description
NEBS	Cisco Firepower 9300 is NEBS compliant with SM-24 Security Modules
Regulatory Compliance	Products comply with CE markings per directives 2004/108/EC and 2006/108/EC

Specification	Description
Safety	<ul style="list-style-type: none"> • UL 60950-1 • CAN/CSA-C22.2 No. 60950-1 • EN 60950-1 • IEC 60950-1 • AS/NZS 60950-1 • GB4943
EMC: Emissions	<ul style="list-style-type: none"> • 47CFR Part 15 (CFR 47) Class A (FCC Class A) • AS/NZS CISPR22 Class A • CISPR22 CLASS A • EN55022 Class A • ICES003 Class A • VCCI Class A • EN61000-3-2 • EN61000-3-3 • KN22 Class A • CNS13438 Class A • EN300386 • TCVN7189
EMC: Immunity	<ul style="list-style-type: none"> • EN55024 • CISPR24 • EN300386 • KN24 • TVCN 7317

Radware DefensePro DDoS Mitigation

Radware DefensePro DDoS Mitigation is available and supported directly from Cisco on the Cisco Firepower 4150 and 9300 with the ASA software image currently, and will also be available on other select Cisco Firepower appliances and the Firepower Threat Defense software image in the future. Radware's DefensePro DDoS mitigation capability is an award-winning, real-time, perimeter attack mitigation solution that secures organizations against emerging network and applications threats. It protects the application infrastructure against network and application downtime (or slow time), helping organizations win the ongoing security battle against availability attacks.

Radware DDoS Mitigation: Protections Set

Radware DDoS mitigation consists of patent-protected, adaptive, behavioral-based real-time signature technology that detects and mitigates zero-day network and application DDoS attacks in real time. It eliminates the need for human intervention and does not block legitimate user traffic when under attack.

The following attacks are detected and mitigated:

- SYN flood attacks
- Network DDoS attacks, including IP floods, ICMP floods, TCP floods, UDP floods and IGMP floods
- Application DDoS attacks, including HTTP floods and DNS query flood
- Anomalous flood attacks, such as nonstandard and malformed packet attacks

Performance

The performance figures in Table 7 are for Cisco Firepower 9300 with a single (SM-24 or SM-36) Security Module.

Table 7. Key DDoS Performance Metrics with Firepower 9300

Parameter	Value
Maximum mitigation capacity/throughput	10 Gbps (30 Gbps with three security modules)
Maximum legitimate concurrent sessions	140,000 connections per second (CPS)
Maximum DDoS flood attack prevention rate	1,200,000 packets per second (PPS)

Ordering Information

Cisco Smart Licensing

The Cisco Firepower NGFW is sold with Cisco Smart Licensing. Cisco understands that purchasing, deploying, managing, and tracking software licenses is complex. As a result, we are introducing Cisco Smart Software Licensing, a standardized licensing platform that helps customers understand how Cisco software is used across their network, thereby reducing your administrative overhead and operating expenses.

With Smart Licensing, you have a complete view of software, licenses, and devices from one portal. Licenses are easily registered and activated and can be shifted between like hardware platforms. Additional information is available here: <http://www.cisco.com/web/ordering/smart-software-licensing/index.html>. Related information, on Smart Licensing Smart Accounts, is available here:

<http://www.cisco.com/web/ordering/smart-software-manager/smart-accounts.html>.

Cisco Smart Net Total Care Support: Move Quickly with Anytime Access to Cisco Expertise and Resources

Cisco Smart Net Total Care™ is an award-winning technical support service that gives your IT staff direct, anytime access to Technical Assistance Center (TAC) engineers and Cisco.com resources. You receive the fast, expert response and the dedicated accountability you require to resolve critical network issues.

Smart Net Total Care provides the following device-level support:

- Global access 24 hours a day, 365 days a year to specialized engineers in the Cisco TAC
- Anytime access to the extensive Cisco.com online knowledge base, resources, and tools
- Hardware replacement options include 2-hour, 4-hour, next-business-day (NDB) advance replacement, as well as return for repair (RFR)
- Ongoing operating system software updates, including both minor and major releases within your licensed feature set
- Proactive diagnostics and real-time alerts on select devices with Smart Call Home

In addition, optional Cisco Smart Net Total Care Onsite Service provides a field engineer to install replacement parts at your location and help ensure that your network operates optimally. For more information on Smart Net Total Care please visit:

<http://www.cisco.com/c/en/us/services/portfolio/product-technical-support/smart-net-total-care.html>.

Select Part Numbers

Tables 8 and 9 provide details on part numbers for Cisco Firepower NGFW solutions. Please consult the Ordering Guide for additional configuration options and accessories.

Table 8. Cisco Firepower 4100 Series: Select Product Components

Part Number (Appliance Master Bundle)	Description
FPR4110-BUN	Cisco Firepower 4110 Master Bundle, for ASA or Cisco Firepower Threat Defense Image
FPR4120-BUN	Cisco Firepower 4120 Master Bundle, for ASA or Cisco Firepower Threat Defense Image
FPR4140-BUN	Cisco Firepower 4140 Master Bundle, for ASA or Cisco Firepower Threat Defense Image
FPR4150-BUN	Cisco Firepower 4150 Master Bundle, for ASA or Cisco Firepower Threat Defense Image
Part Number (Spare Network Module)	Description
FPR4K-NM-8X10G=	Spare Cisco Firepower 8-port SFP+ network module
FPR4K-NM-4X40G=	Spare Cisco Firepower 4-port QSFP+ network module
Hardware Accessories	
Please consult the ordering guide for accessories including rack mounts, spare fans, power supplies, and solid-state drives (SSDs)	
Optional ASA Software Licenses	Description
L-F4K-ASA-CAR	License to add Carrier Security Features to ASA
L-FPR4K-ENCR-K9	License to enable strong encryption for ASA on Cisco Firepower 4100 Series
L-FPR4K-ASASC-10	Cisco Firepower 4100 Add-on 10 Licenses
Cisco Firepower 4100 Series NGFW Select Licenses	
L-FPR4110T-TMC=	Cisco Firepower 4110 Threat Defense Threat, Malware, and URL License
L-FPR4120T-TMC=	Cisco Firepower 4120 Threat Defense Threat, Malware, and URL License
L-FPR4140T-TMC=	Cisco Firepower 4140 Threat Defense Threat, Malware, and URL License
L-FPR4150T-TMC=	Cisco Firepower 4150 Threat Defense Threat, Malware, and URL License
Note: These optional security services licenses can be ordered with 1-, 3-, or 5-year subscriptions.	

Table 9. Cisco Firepower 9300: Select Product Components

Part Number (Chassis)	Description
FPR-C9300-AC	Cisco Firepower 9300 AC Chassis (3RU; accommodates up to three security modules)
FPR-C9300-DC	Cisco Firepower 9300 DC Chassis (3RU; accommodates up to three security modules)
Part Number (Module)	Description
FPR9K-SM-24	24 Physical Core Security Module (NEBS Ready)
FPR9K-SM-36	36 Physical Core Security Module
ASA Software Licenses for Cisco Firepower 9300	Description
L-ASA-CARRIER	License to add Carrier Security Features to ASA
L-ASA-CARRIER=	License to add Carrier Security Features to ASA
L-FPR9K-ASA-SC-10	License to add 10 Security Contexts to ASA in Cisco Firepower 9000
L-FPR9K-ASA-SC-10=	License to add 10 Security Contexts to ASA in Cisco Firepower 9000
L-FPR9K-ASA	License to run Standard ASA on a Cisco Firepower 9300 module
L-FPR9K-ASA=	License to run Standard ASA on a Cisco Firepower 9300 module
L-FPR9K-ASAENCR-K9	License to enable strong encryption in ASA running on Cisco Firepower 9000

Cisco Firepower 9300 NGFW Threat Defense Software Licenses	Description
FPR4110T-BASE	Cisco Firepower Threat Defense Base License for Cisco Firepower 9300 NGFW
L-FPR9K-SM24-TMC=	Cisco Firepower 9000 SM-24 Threat Defense Threat, Malware, and URL License
L-FPR9K-SM24-TMC-3Y	Cisco Firepower 9000 SM-24 Threat Defense Threat, Malware, and URL 3Yr Svc
L-FPR9K-SM36-TMC=	Cisco Firepower 9000 SM-36 Threat Defense Threat, Malware, and URL License
L-FPR9K-SM36-TMC-3Y	Cisco Firepower 9000 SM-36 Threat Defense Threat, Malware, and URL 3Yr Svc

Warranty Information

Find warranty information on cisco.com at the [Product Warranties](#) page.

Cisco Services

Cisco offers a wide range of service programs to accelerate customer success. These innovative services programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco Services help you protect your network investment, optimize network operations, and prepare your network for new applications to extend network intelligence and the power of your business. For more information about Cisco services for security, visit <http://www.cisco.com/go/services/security>.

Cisco Capital

Financing to Help You Achieve Your Objectives

Cisco Capital[®] financing can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx. Accelerate your growth. Optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries. [Learn more.](#)

More Information for Service Providers

For information about Cisco Firepower in Service Provider environments, please visit:

- <http://www.cisco.com/c/en/us/solutions/enterprise-networks/service-provider-security-solutions/>

More Information about Firepower NGFWs

For further information about Cisco Firepower NGFWs, please visit:

- <http://www.cisco.com/go/ngfw>

More Information about Cisco AnyConnect

- Cisco AnyConnect Secure Mobility Client
<http://www.cisco.comhttp://www.cisco.com/go/anyconnect/go/anyconnect>.
- Cisco AnyConnect Ordering Guide
<http://www.cisco.com/c/dam/en/us/products/security/anyconnect-og.pdf>.




Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

 Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)